

RECHARGEABLE

INTRANT® DUAL-LIGHT ANGLE LIGHT

NIGHTSTICK
Life Depends on Light



HEAD ROTATES 90°

45°


EXCLUSIVE
DOWNWARD FLOODLIGHT



Charging Status Indicator – Two LEDs turn red when charging, switching to green when full



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches **independently control** separate LEDs

GRAB-N-GO
CHARGING BASE



Heavy-duty, clip and V-ring **securely holds tight to turnout gear**



ALSO AVAILABLE IN SAFETY RED

300 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

DUAL-LIGHT ANGLE LIGHT

RECHARGEABLE

ITEM NUMBER

- XPR-5569RX (Red)
- XPR-5569GX (Green)

PATENTS

- 9,713,217 10,119,663

CHARGING STATUS INDICATOR

- The Charging Status Indicator has two LEDs on either side that show red or green light. Turns red while charging and switches to green when fully charged

LOW BATTERY FLASHING

- Angle light flashes three times to signal when battery reaches 20%

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 300L, 8 hrs. runtime
- MEDIUM: 110L, 15 hrs. runtime
- LOW: 60L, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 180L, 7 hrs. runtime
- MEDIUM: 40L, 15 hrs. runtime
- SURVIVAL: 25L, 27 hrs. runtime

DUAL-LIGHT

- 270L, 7 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 10.6 oz (301g)(with batteries)

BATTERY







- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	300 LUMENS	60 LUMENS	270 LUMENS
	8	27	7
	401m		
	40256cd		
	2m		
	1m		

CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV1 GRPS E-G T135°C
 CLASS I ZONE 0 AEx ia IIC T4 Ga
 ZONE 20 AEx ia IIIC T135°C Da
 Ⓢ I M1 Ex ia I Ma
 Ⓢ II 1 G Ex ia IIC T4 Ga
 Ⓢ II 1 D Ex ia IIIC T135°C Da